012745491 **Image available**
WPI Acc No: 1999-551608/199947
Related WPI Acc No: 1999-419539

XRAM Acc No: C99-161132 XRPX Acc No: N99-408232

Mold plate production for use in manufacture of chocolate products

Patent Assignee: BRABHAM PROMOTIONS PTY LTD (BRAB-N)

Inventor: BRABHAM G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
AU 9932358 A 19990826 AU 9918443 A 19990225 199947 B
AU 9932358 A 19990531

Priority Applications (No Type Date): AU 987517 A 19981204

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

AU 9932358 A 27 B29C-033/38 Div ex application AU 9918443 Div ex patent AU 706808

Abstract (Basic): AU 9932358 A

NOVELTY - Production of a mold plate comprises irradiating a photopolymeric printing plate (10) with UV radiation through a positive film (8) with an image of the chocolate design on it. The plate is then washed to remove uncured polymer to define a relief mold cavity on the plate. The plate is dried and post-exposed to hardened or uncured polymer

DETAILED DESCRIPTION - Production of a mold plate comprises:

- (i) providing an image on a film of the design to be reproduced, contrasting with the film background, whereby either the image or the background is transparent while the other being dark, with a plate of photopolymeric polymer to cure and harden on exposure to UV radiation;
- (ii) positioning the film between a UV source and the photopolymeric plate with the film in alignment with the printing plate;
- (iii) irradiating the film with UV radiation such that the radiation passes through the transparent areas of the film and irradiates the corresponding portion of the photopolymeric plate, and radiation is blocked by the dark areas on the film so that the corresponding portion of the photopolymeric plate is not irradiated;
- (iv) washing the photopolymeric plate to remove soft uncured polymer from the printing plate to define a relief mold; and
- (v) drying and post-exposing the photopolymeric plate to give a hard relief mold surface which can be used in the production of chocolate products.

INDEPENDENT CLAIMS are also included for:

- (I) the production of a chocolate product; and
- (\mbox{II}) a process for reproducing an image from a film on a chocolate product.

USE - For the production of mold plates for use in the production of chocolate products, or for reproducing an image from a film on a chocolate product.

ADVANTAGE - The mold plates can be used to produce very clean and sharp logo image chocolates, e.g. single tone pictures. The cost of

producing the plate is lower than that for an engraved mold plate. It is possible to tool up a mold plate to produce a new design for a chocolate product much quicker than when engraving is used. It can be used to produced photograph-like or real life pictures.

DESCRIPTION OF DRAWING(S) - The figure shows a schematic three dimensional view of a machine for carrying out the process.

Film (8)

Photopolymeric plate (10)

pp; 27 DwgNo 1/5

Technology Focus:

TECHNOLOGY FOCUS - FOOD - Preferred Process: The image on the film is dark and the background is transparent, and the second mold plate is bendable or deformable. The plates are washed for 350-400 seconds during the washing step. UV radiation is directed into the photopolymeric plate at an angle to cause the polymer to cure in an angled line rather than a vertically extending line. The angling of UV radiation is accomplished by placing a transparent sheet over the positive film during irradiation with UV radiation so that the rays of UV radiation are directed inwardly by refraction.

Title Terms: PLATE; PRODUCE; MANUFACTURE; CHOCOLATE; PRODUCT

Derwent Class: A32; A35; A97; D13; G06; P84

International Patent Class (Main): B29C-033/38

International Patent Class (Additional): A23G-001/20; A23G-001/21;

G03F-007/038; G03F-007/30

File Segment: CPI; EngPI

Manual Codes (CPI/A-N): A11-C02B; A12-H05; A12-L02; A12-W09; D03-E03;

D03-E07; G06-F03C; G06-G17; G06-G18

Polymer Indexing (PS):

<01>

001 018; P0000; M9999 M2073; K9869 K9847 K9790; L9999 L2391; L9999 L2073; K9723

002 018; ND01; K9483-R; K9676-R; K9712 K9676; Q9999 Q7114-R; Q9999 Q7589-R; Q9999 Q7932 Q7885; Q9999 Q8684 Q8673 Q8606; N9999 N5889-R; B9999 B3792 B3747

?